



# ShieldSeal PU-320

## Anti-Slip Additive

info@shieldcreteinternational.com  
www.shieldcreteinternational.com

### Product Description

ShieldSeal PU-305V is an additive that provides anti-slip properties to the floor coatings systems.

### Main Applications

Recommended in floors of warehouses, industrial facilities, food industry, garages and stairs. It can be used with epoxy, polyurethane, acrylic and chlorinated rubber coatings.

### Properties

<b>Colour</b>	White
<b>Average Particle Size</b>	150 µm
<b>Bulk Density</b>	1.500 g/mL

### Applications

Add the additive C-Floor Anti-Slip Additive 150 to the coating with mechanical stirring until a homogeneous mixture is obtained. The amount to be mixed in the coatings varies depending on the type of coating and the anti-slip properties desired. The coating will have to be further diluted in order to allow a good application, normally 5 % more than usual.

For further information please check the Technical Data Sheet of the coating.

### Packaging

Product : 1.5 and 6.0 kg

### Storage

Product : 5 years, stored in the original containers, without opening, indoors, between 5 and 40 °C

### Health, Safety and the Environment

Protect the eyes and skin from contact. Gloves, goggles and appropriate clothing should be worn. Keep out of the reach of children. Use only in well-ventilated areas. Do not empty into drains. Keep the container properly sealed and stored in the correct place. Take correct measures when transporting the product so as to avoid any accidents that could rupture the can or cause damage to the packaging. Ensure that the container is correctly stacked in a safe area. Do not store or use the product in extreme temperature conditions. Always take account of the appropriate legislation relating to the environmental and Health and Safety at Work. For more information it is essential to read the label on the container and the product Material Safety Data Sheet of this product, its components and all complementary products referred on Technical Data Sheet.

### DISCLAIMER

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials and equipment used, as well as varying working conditions and environments beyond our control we strictly recommend carrying out intensive trials to test the suitability of our products regarding the required processes and applications. This data sheet is provided free of charge, and we do not accept any liability regarding the above information or regarding any verbal recommendation, except for cases where we are liable of gross negligence or false intention.