

SAFETY DATA SHEET 2025

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

| | |
|--|--|
| Product Name | : ShieldFix BF |
| Other means of Identification | : None |
| Component | : Cure |
| Relevant identified uses of the substance or mixture and uses advised against | : No further relevant information available |
| Application of the Substance / Mixture | : Filler |
| Manufacturer/Importer/Supplier/Distributor | |
| Name | : ShieldCrete® International |
| Company Name | : ShieldCrete® International Sdn Bhd |
| Address | : No. 14, Jalan Anggerik Mokara 31/60, Kota Kemuning Industry Area, 40460 Shah Alam, Selangor, Malaysia |
| Contact Numbers | : +6(03) 5131 2101 |
| Email | : info@shieldcreteinternational.com |
| Website | : www.shieldcreteinternational.com |

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification according to Regulation (EC) No 1272/2008



GHS08 Health Hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.
 Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
 Skin Sens. 1 H317 May cause an allergic skin reaction.

Label Elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard Pictograms:

GHS05



GHS07



GHS08



Signal Word:

Warning

Hazard-determining Components of Labelling:

- IPDA-BADGE-BUMGE
- quartz (SiO₂) (fine fraction)
- Benzyl Alcohol

Hazard Statements:

- Harmful if swallowed.
- Causes severe skin burns and eye damage.
- May cause an allergic skin reaction.
- May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

- Do not breath dusts or mists.
- Wear protective gloves / eye protection / face protection.

If on Skin (or Hair): Take off immediately all contaminated clothing. Rinse skin with water [or Shower].





If in Eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Dispose of contents/container in accordance with regional/national regulations.

Other Hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: COMPOSITES / INFORMATION ON INGREDIENTS**Mixtures**

Description: Mixture of substances listed below with nonhazardous additions.

| DANGEROUS COMPONENTS | | |
|--|--|--------|
| Reg.nr.: 01-2119972329-26 | IPDA-BADGE-BUMGE  Skin Corr. 1C, H314; Eye Dam. 1, H318;  Acute Tox. 4, H302; Skin Sens. 1, H317 | 25-50% |
| CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38 | Benzyl Alcohol  Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 | 25-50% |
| CAS: 7727-43-7 EINECS: 231-784-4 Reg.nr.: 01-2119491274-35 | Barium Sulfate substance with a community workplace exposure limit | 25-50% |
| CAS: 14808-60-7 EINECS: 238-878-4 Reg.nr.: - | Quartz (SiO ₂) (fine fraction)  STOT RE 1, H372 | 25-50% |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: FIRST AID MEASURES

- General Information:** Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident.
- Inhalation:** Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- Skin Contact:** Immediately wash with water and soap and rinse thoroughly.
- Eye Contact:** Rinse opened eye for several minutes under running water. Then, consult a doctor.
- Ingestion:** Call for a doctor immediately.
- Most important symptoms and effects, both acute and delayed:**
No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:**
No further relevant information available.

SECTION 5: FIRE FIGHTING MEASURES

- Extinguishing Media:**
Use fire extinguishing methods suitable to surrounding conditions.
- Special Hazards arising from the Substance or Mixture:**
During heating or in case of fire poisonous gases are produced.
- Advice for Firefighters:**
Protective equipment: Mount respiratory protective device.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions, Protective Equipment, and Emergency Procedures:**
Mount respiratory protective device.
- Environmental Precautions:**
Do not allow to enter sewers/ surface or ground water.
- Methods and Material for Containment and Cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent. Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- Reference to other sections:**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: HANDLING AND STORAGE

- Precautions for Safe Handling:**
Ensure good ventilation/exhaustion at the workplace.
Avoid inhalation of spray application of the product.
To remove contaminated clothing and protective equipment before entering eating areas.
To wash hands after use.
Not to eat, drink and smoke in work areas.
- Information about fire - and explosion protection:** Keep respiratory protective device available.

Conditions for Safe Storage, including any incompatibilities:
Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s):

No further relevant information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

Control Parameters:
Ingredients with limit values that require monitoring at the workplace:
CAS: 7727-43-7 Barium Sulfate

WEL Long-term value: 10* 4** mg/m³

*Inhalable dust **Respirable dust

| DNELs | | |
|-------------------------------|---|---|
| CAS: 100-51-6 Benzyl Alcohol | | |
| Oral | DNEL Long term systemic effects | 4 mg/kg/day/ (consumers) |
| | DNEL Short term systemic effects | 10-40 mg/kg/day/ (consumers) |
| Dermal | DNEL Long term systemic effects | 4 mg/kg bw/24h/ (consumers) |
| | DNEL Short term systemic effects | 5.5-24.5 mg/kg bw/24h/ (workers) |
| Inhalative | DNEL Long term systemic effects | 13.5-43.5 mg/kg/ bw/24h/ (consumers) |
| | DNEL Short term systemic effects | 32-62 mg/kg/ bw/24h/ (workers) |
| | DNEL Long term systemic effects | 5.4 mg/m ³ / (consumers) |
| | DNEL Short term systemic effects | 22 mg/m ³ / (workers) |
| | | 13.5-43.5 mg/m ³ / (consumers) |
| | | 110 mg/m ³ / (workers) |
| CAS: 7727-43-7 Barium Sulfate | | |
| Oral | DNEL Long term systemic effects | 13,000 mg/kg/day/ (consumers) |
| Inhalative | DNEL Long term systemic effects | 10 mg/m ³ / (consumers) |
| | | 10 mg/m ³ / (workers) |
| | DNEL Short term systemic effects | 10 mg/m ³ / (workers) |
| PNECs | | |
| CAS: 100-51-6 Benzyl alcohol | | |
| PNEC water | 14-16 mg/l/ (freshwater) | |
| | 14.9-15.1 mg/l (marine water) | |
| | 12.7-17.3 mg/l/ (intermittent release) | |
| PNEC sediment | 14.47-15.53 mg/kg/ (marine sediment) | |
| | 9.73-20.27 mg/kg/ (freshwater sediment) | |
| PNEC STP | 24-54 mg/l/ (sewage treatment plant) | |
| PNEC Soil | 14.54-15.46 mg/kg/ (soil) | |

Additional information: The lists valid during the making were used as basis.

Exposure Controls:
Personal Protective Equipment
General Protective and Hygienic Measures:

Keep away from foodstuffs, beverages, and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory Protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of Hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye Protection:

Tightly sealed goggles.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**Information on Basic Physical and Chemical Properties**

| | |
|--|--|
| Appearance | Fluid |
| Color | According to product specification |
| Odor | Characteristic |
| Odor Threshold | Not determined |
| pH Value | Not determined |
| Melting Point / Freezing Point | Undetermined |
| Initial Boiling Point and Boiling Range | 205.4°C |
| Flash Point | 131°C |
| Flammability (solid, gas) | Not applicable |
| Decomposition Temp | Not determined |
| Auto-ignition Temp | Product is not self-igniting |
| Explosive Properties | Product does not present an explosion hazard |
| Explosion Limits (Lower) | 1.3 Vol % |
| Explosion Limits (Upper) | 13 Vol % |
| Vapor Pressure at 20°C | 0.1 hPa |
| Density at 20°C | 1.421 g/cm ³ |
| Relative Density | Not determined |
| Vapor Density | Not determined |
| Evaporation Rate | Not determined |

| | |
|---|----------------------------------|
| Solubility in / Miscibility with Water | Not miscible or difficult to mix |
| Partition Coefficient: N-octanol/Water | Not determined |
| Solids Content (w/w) | 73.6 % |

Other information: The provisions of directive 2004/42/CE on VOC apply to this product. Refer to the product label and /or technical data sheet for further information.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: No further relevant information available.

Chemical Stability:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: No dangerous reactions known.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: No dangerous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Acute Toxicity: Harmful if swallowed.

| LD/LC50 Values Relevant for Classification | | |
|--|------|----------------------|
| CAS: 100-51-6 Benzyl Alcohol | | |
| Oral | LD50 | 500 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

Primary Irritant Effect:

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/irritation: Causes serious eye damage.

Respiratory or skin sensitization: May cause an allergic skin reaction.

CMR Effects (Carcinogenicity, Mutagenicity and Toxicity for Reproduction)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

| Aquatic Toxicity | |
|------------------|---|
| IPDA-BADGE-BUMGE | |
| EC50/48 h | >10 mg/l/ (daphnia magna) |
| EC50/72 h | 2.1 mg/l/ (pseudokirchneriella subcapitata (algae)) |
| LC50/96 h | >10 mg/l/ (cyprinus carpio) |

| CAS: 100-51-6 Benzyl Alcohol | |
|------------------------------|---------------------------|
| EC50/24 h | 390 mg/l/ (bacterium) |
| EC50/48 h | 230 mg/l/ (daphnia magna) |
| EC50/72 h | 700 mg/l/ (algae) |
| LC50/96 h | 460 mg/l/ (fish) |

Persistence and Degradability: No further relevant information available.

Bioaccumulative Potential: No further relevant information available.

Mobility in Soil: No further relevant information available.

Additional Ecological Information

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unnaturalized.

Results of PBT and vPvB Assessment: PBT: Not applicable.
vPvB: Not applicable.

Other Adverse Effects: No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Product

Recommendation: Disposal must be made according to official regulations.
Must not be disposed together with household garbage.
Do not allow product to reach sewage system.
The information given is based on Directive (EU) 2008/98.

European Waste Catalogue: This product is considered hazardous waste as defined by EU Directive 2008/98/EC.

European Waste Catalogue: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances.

Uncleaned Packaging

Recommendation: Disposal must be made according to official regulations.
The package should be properly drained.

SECTION 14: TRANSPORT INFORMATION

UN Number

ADR, IMDG, IATA UN3066

UN Proper Shipping Name

ADR 3066 PAINT
IMDG, IATA PAINT

Transport Hazard Class(es)

ADR, IMDG, IATA



Class 9 Miscellaneous dangerous substances and articles.
Label 9

Packing Group

ADR, IMDG, IATA III

Environmental Hazards Not applicable.

Special Precautions for User

Warning: Warning: Corrosive substances.
Danger Code (Kemler): 80
EMS Number: F-A, S-B
Stowage Category: A
Stowage Code: SW2 Clear of living quarters.

Transport in bulk according to ANNEX II of Marpol and the IBC Code

Not Applicable

Transport/Additional Information:
ADR

| | |
|---------------------------------|--|
| Limited Quantities (LQ) | 5L |
| Excepted Quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport Category | 3 |
| Tunnel Restriction Code | E |

IMDG

| | |
|---------------------------------|--|
| Limited Quantities (LQ) | 5L |
| Excepted Quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation" | UN 3066 PAINT, 8, III |

SECTION 15: REGULATORY INFORMATION

Safety, Health, and Environmental Regulations/Legislation specific for the Substance or Mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I

None of the ingredients is listed.

List of substances subject to authorization (ANNEX XIV)

None of the ingredients is listed.

Regulation (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

Waterhazard Class

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Other regulations, limitations, and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.

- H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H372 Causes damage to organs through prolonged or repeated exposure

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Acute toxicity - oral
- Skin corrosion/irritation
- Serious eye damage/eye irritation
- Skin sensitization
- Specific target organ toxicity (repeated exposure)

Abbreviations and Acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2